

TECHNICAL SPECIFICATION

PYROMASTER SLAVE24



Firmware version:

1.4.x

Hardware version:

1324

Document revision:

1.4

1. **Features:**

1.1. Available operating modes:

- Manual (remote)
- Semi-Automatic (external trigger button)
- Sequential (remote or external trigger button)
- Automatic (remote or external trigger button)

1.2. Arming:

- locally (front-panel button)
- remotely (from Master unit)

1.3. Triggering/Firing:

- remotely (from Master unit)
- locally (external trigger button)

1.4. Channel count: 24

1.5. Max. sequences count: 24

1.6. Sequence designation range: 1 – 1023

1.7. Maximum duration of single sequence: 9:59,99

1.8. Maximum duration of automatic program: 9:59:59,99

1.9. Maximum resolution of programmed sequence: 0,01s (10ms)

1.10. Maximum resolution of automatic program 0,01s (10ms)

1.11. Adjustable channel activation time: yes (0,1s – 2,5s)

1.12. Continuous time synchronisation with Master unit during ongoing show: yes

1.13. Igniter tests:

- Automatic (all channels)
- According to automatic program
- According to chosen sequence
- Manual (single channel)
- Remote (from Master unit)

- 1.14. Replicator igniter test: yes
- 1.15. External trigger button test: yes
- 1.16. Igniter firing voltage: 24V
- 1.17. Maximum igniter count per channel: over 20
- 1.18. Igniter test current: max 3mA
- 1.19. Preview, edit and deletion of automatic program directly in the unit: yes
- 1.20. Preview, edit and deletion of sequences directly in the unit: yes
- 1.21. Preview, adding and removal of Replicator units: yes
- 1.22. Editing of Replicator channels directly in Slave unit: yes
- 1.23. Replicator connection confirmation: yes
- 1.24. Support for safety zones: yes
- 1.25. Radio channel selection: yes
- 1.26. Display backlit regulation: yes
- 1.27. Battery charge display: yes
- 1.28. Keyboard confirmation sound: yes
- 1.29. Arm sound alert: yes
- 1.30. Standby mode: yes
- 1.31. Standby mode activation/deactivation:
 - Locally
 - Remotely (from Master unit)

2. **Radio link:**

- 2.1. Radio frequency: 869MHz
- 2.2. Available radio channels: 9
- 2.3. Maximum transmitter power: 500mW (27dBm)
- 2.4. Receiver sensitivity: -116dBm @BER 10^{-3}
- 2.5. Adjustable transmitter power: yes
- 2.6. Range in dense urban environment (without direct line-of-sight): approx. 1-2km
- 2.7. Range in open area (direct antenna line-of-sight): up to 10km
- 2.8. Transmission type: bidirectional
- 2.9. Transmission security: encryption, checksum, acknowledgements
- 2.10. Automatic switch to wired communication: yes

3. **Wired link - Master Line:**

- 3.1. Physical layer: RS485 (differential transmission)
- 3.2. Automatic line termination: yes
- 3.3. Master Line input count: 1
- 3.4. Master Line output count: 2
- 3.5. Maximum unit count connected to single output: 32
- 3.6. Maximum line length between neighbouring units: 1,2km
- 3.7. Transmission type: bidirectional
- 3.8. Transmission security: encryption, checksum, acknowledgements
- 3.9. Signal booster feature: yes
- 3.10. Splitter feature: yes
- 3.11. Retransmission of radio signal on wired output: yes
- 3.12. Retransmission of wired signal on radio link: yes
- 3.13. Automatic switch to radio communication: yes

4. **Wired link - Replicator Line:**

- 4.1. Physical layer: RS485 (differential transmission)
- 4.2. Automatic line termination: yes

- 4.3. Replicator Line output count: 3
- 4.4. Maximum unit count connected to single output: 32
- 4.5. Maximum number of supported Replicator units: 32
- 4.6. Maximum line length: 1,2km
- 4.7. Transmission type: bidirectional
- 4.8. Transmission security: encryption, checksum, acknowledgements
- 5. USB communication:**
 - 5.1. USB device mode: yes
 - 5.2. USB connector style: B
 - 5.3. Automatic program upload: yes
 - 5.4. Sequence upload: yes
 - 5.5. Transmission security: encryption, checksum, acknowledgements
- 6. Protection:**
 - 6.1. ESD (Electrostatic Discharge) protection
 - 6.2. Resistance to shock and weather conditions
 - 6.3. Channel short-circuit protection
 - 6.4. Safe igniter test (maximum test current control, igniter test forbidden in armed mode)
 - 6.5. System auto-diagnostics
 - 6.6. Self error prompts (e.g. arm error, controller error)
 - 6.7. Replicator error prompts (e.g. arm error, low battery)
 - 6.8. Error reports directly to Master unit
 - 6.9. Data transmission encryption
- 7. Other:**
 - 7.1. Continuous operation on single battery charge: approx. 120h
 - 7.2. Continuous operation in standby mode on single battery charge: approx. 330h
 - 7.3. Battery charge voltage: 24V
 - 7.4. Menu language: polish, english
 - 7.5. LCD display backlight: yes
 - 7.6. Membrane keyboard: yes
 - 7.7. Front panel LED indicators: yes
 - 7.8. LED channel activation indicator of each single channel: yes
 - 7.9. External housing LED indicators: yes
 - 7.10. External antenna: yes
 - 7.11. Antenna connector style N
 - 7.12. Housing: Peli case (durable, water-resistant)
 - 7.13. Igniter connectors: metal, stringed
 - 7.14. Weight: 7,6kg
 - 7.15. Dimensions: 35x30x15cm
 - 7.16. Working temperature range: -20°C do +40°C